

BATTERY-BOX PREMIUM LVL (2021)

- Scalable from 15.4 to 983 kWh
- Compatible with 1 and 3 Phase Inverters
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle, and Power
- Capable of High-Powered Back-up and Off-Grid Function
- Space Saving via the Ability to Stack 2 Premium Batteries
- Add Additional Batteries in Parallel to Expand the System



BATTERY-BOX PREMIUM LVL (2021)

The BYD Battery-Box Premium LVL is a lithium iron phosphate (LFP) battery for use with an external inverter.

Thanks to its control and communication unit (BMU), the Battery-Box Premium LVL scales to meet the project requirements, no matter how large they may be. Start with Battery-Box Premium LVL15.4 (15.36 kWh) and extend later to 983 kWh using parallel interconnection of up to 64 batteries.



FLEXIBLE, EFFICIENT, SIMPLE



Easy Installation
With Easy Transportation



15.4 - 983 kWh
Tailored Sizing for Each Application



Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS PREMIUM LVL (2021)



LVL15.4

Number of Modules	2
Usable Energy [1]	15.36 kWh
Max Cont. Output Current [2]	250 A
Peak Output Current [2]	375 A, 5 s
Dimensions (H/W/D)	660 x 650 x 575 mm
Weight	168 kg
Nominal Voltage	51.2 V
Operating Voltage	40-57.6 V
Operating Temperature	-10 °C to +50°C
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)
Communication	CAN/RS485
Enclosure Protection Rating	IP20
Round-trip Efficiency	≥95%
Scalability	Max. 64 in Parallel (983 kWh)
Certification	IEC62619 / CE / CEC / UN38.3
Applications	ON Grid / ON Grid + Backup / OFF Grid
Warranty [3]	10 Years
Compatible Inverters	Refer to BYD Battery-Box Premium LVL Minimum Configuration List

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System usable energy may vary due to system configuration parameters.

[2] Charge derating will occur between -10 °C and +5 °C

[3] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.

